

# Specification Sheet

Model # FC46S-4FR-A



# MISCO®

## Key Features:

- 4 X 6" (100 X 156 mm), 4 ohm
- Voice Range, 12 watts
- Ferrite magnet, flame retardant paper cone;

## Product Specifications & Parameters

### Primary Specifications

Speakers Environment	Indoor
RoHS Compliant	No

### Technical Specifications

		Units of Measure
Nominal Basket Diameter	4.0 x 6.0	inch
	100.0 x 156.0	mm
Rated Impedance	4	ohms
Rated Power	12.0	Watts
Program Power	24	Watts
Frequency Range	200 - 6000	Hz
Sensitivity (2.83 V input measured at 1 Meter)	94	dB SPL
Voice Coil Diameter	0.8 / 20.3	inch / mm
Magnet Weight	4.8 / 136	oz / gr
Transformer		


### Small Signal Parameters

		Units of Measure
Resonant Frequency (fo)	297	Hz
D.C. Resistance (Re)	3.0	ohms
Mechanical Q (Qms)	6.7	
Electrical Q (Qes)	2.31	
Total Q (Qts)	1.72	
Compliance Equivalent Volume (Vas)		ltr
BL Product (BL)		T-M
Maximum Linear Excursion (Xmax)	0.0	mm
Surface Area of Cone (Sd)		cm <sup>2</sup>
Moving Mass (Mmd)		g

### Material Descriptions

Basket	Stamped Steel
Terminal Size	0.19 X 0.02
Magnet	Ferrite
Voice Coil Wire	Copper
Voice Coil Form	Aluminum
Cone	Flame Retardant Paper
Cone Edge	Paper
Dust Cap	Paper

## Sensitivity / Frequency



## Drawing

ID	Description	Measurements	Tolerance
Od	Outside Diameter	6.1 in.	+/- 0.020"
CD	Cutout Diameter	5.8 in.	+/- 0.020"
MG	Magnet Diameter	2.8 in.	+/- 0.050"
HD	Hole Diameter	0.2 in.	+/- 0.010"
MD	Mounting Diameter	5.2 in.	+/- 0.010"
ID	Internal Depth	1.5 in.	+/- 0.025"
FT	Flange Thickness	0.2 in.	+/- 0.050"
NW	Net Weight	485.0 g	

