

Specification Sheet

Model # EC5FR



MISCO®

Key Features:

- 4.5" (115mm), 8 ohm
- Voice Range, 6 watts
- Ferrite magnet, flame retardant paper cone;

Product Specifications & Parameters

Primary Specifications

Speakers Environment	Indoor
RoHS Compliant	No

Technical Specifications

		Units of Measure
Nominal Basket Diameter	4.5	inch
	115.0	mm
Rated Impedance	8	ohms
Rated Power	6.0	Watts
Program Power	12	Watts
Frequency Range	170 - 10000	Hz
Sensitivity (2.83 V input measured at 1 Meter)	92	dB SPL
Voice Coil Diameter	0.8 / 20.3	inch / mm
Magnet Weight	3.0 / 85	oz / gr
Transformer		

Small Signal Parameters

		Units of Measure
Resonant Frequency (fo)	200	Hz
D.C. Resistance (Re)	6.0	ohms
Mechanical Q (Qms)		
Electrical Q (Qes)		
Total Q (Qts)		
Compliance Equivalent Volume (Vas)		ltr
BL Product (BL)		T-M
Maximum Linear Excursion (Xmax)	0.4	mm
Surface Area of Cone (Sd)		cm ²
Moving Mass (Mmd)		g

Material Descriptions

Basket	Stamped Steel
Terminal Size	0.19 x 0.02
Magnet	Ferrite
Voice Coil Wire	Copper
Voice Coil Form	Aluminum
Cone	Flame Retardant Paper
Cone Edge	Flame Retardant Paper
Dust Cap	Flame Retardant Paper

Drawing

ID	Description	Measurements	Tolerance
OD	Outside Diameter	4.7 in.	+/- 0.040"
CD	Cutout Diameter	4.4 in.	+/- 0.030"
MG	Magnet Diameter	2.4 in.	+/- 0.050"
HD	Hole Diameter	0.4 in.	+/- 0.020"
MD	Mounting Diameter	4.7 in.	+/- 0.020"
ID	Internal Depth	1.6 in.	Maximum
FT	Flange Thickness	0.1 in.	+/- 0.050"
NW	Net Weight	333.0 gr.	

