

Specification Sheet

Model # EN4S-4FR



MISCO®

Key Features:

- 4" (100mm), 4 ohm
- Voice Range, 12 watts
- Neodymium magnet, flame retardant paper cone;

Product Specifications & Parameters

Primary Specifications

Speakers Environment	Indoor
RoHS Compliant	No

Technical Specifications

		Units of Measure
Nominal Basket Diameter	4.0	inch
	100.0	mm
Rated Impedance	4	ohms
Rated Power	12.0	Watts
Program Power	24	Watts
Frequency Range	200 - 8000	Hz
Sensitivity (2.83 V input measured at 1 Meter)	88	dB SPL
Voice Coil Diameter	0.8 / 20.3	inch / mm
Magnet Weight	0.4 / 12	oz / gr
Transformer		


Small Signal Parameters

		Units of Measure
Resonant Frequency (fo)	276	Hz
D.C. Resistance (Re)	3.0	ohms
Mechanical Q (Qms)	6.7	
Electrical Q (Qes)	2.45	
Total Q (Qts)	1.79	
Compliance Equivalent Volume (Vas)		ltr
BL Product (BL)		T-M
Maximum Linear Excursion (Xmax)	1.3	mm
Surface Area of Cone (Sd)		cm ²
Moving Mass (Mmd)		g

Material Descriptions

Basket	Stamped Steel
Terminal Size	0.205 X 0.02
Magnet	Neodymium
Voice Coil Wire	Copper
Voice Coil Form	Aluminum
Cone	Flame Retardant Paper
Cone Edge	Paper
Dust Cap	Paper

Sensitivity / Frequency



Drawing

ID	Description	Measurements	Tolerance
Od	Outside Diameter	4.1 in.	+/- 0.020"
CD	Cutout Diameter	3.8 in.	+/- 0.020"
MG	Magnet Diameter	1.1 in.	+/- 0.050"
HD	Hole Diameter	0.2 in.	+/- 0.010"
MD	Mounting Diameter	4.7 in.	+/- 0.010"
ID	Internal Depth	1.2 in.	+/- 0.025"
FT	Flange Thickness	0.1 in.	+/- 0.050"
NW	Net Weight	104.0 g	

