

# Specification Sheet

Model # KC42C-8A



# MISCO®

## Key Features:

- 4.5" (115mm), 8 ohm
- Full Range, 40 watts
- Ferrite magnet, Paper cone with cloth surround;

## Product Specifications & Parameters

### Primary Specifications

Speakers Environment	Indoor
RoHS Compliant	No

### Technical Specifications

		Units of Measure
Nominal Basket Diameter	4.5	inch
	115.0	mm
Rated Impedance	8	ohms
Rated Power	40.0	Watts
Program Power	80	Watts
Frequency Range	90 - 16,000	Hz
Sensitivity (2.83 V input measured at 1 Meter)	90	dB SPL
Voice Coil Diameter	1.0 / 25.4	inch / mm
Magnet Weight	12.0 / 341	oz / gr
Transformer		


### Small Signal Parameters

		Units of Measure
Resonant Frequency (fo)	117	Hz
D.C. Resistance (Re)	6.6	ohms
Mechanical Q (Qms)	8.5	
Electrical Q (Qes)	0.68	
Total Q (Qts)	0.63	
Compliance Equivalent Volume (Vas)	3.0	ltr
BL Product (BL)	5.0	T-M
Maximum Linear Excursion (Xmax)	0.9	mm
Surface Area of Cone (Sd)	64.0	cm <sup>2</sup>
Moving Mass (Mmd)		g

### Material Descriptions

Basket	Stamped Steel
Terminal Size	0.205 x 0.02
Magnet	Ferrite
Voice Coil Wire	Copper
Voice Coil Form	Kapton
Cone	Paper
Cone Edge	Cloth
Dust Cap	Paper

# Sensitivity / Frequency



# Drawing

ID	Description	Measurements	Tolerance
Od	Outside Diameter	4.6 in.	+/- 0.020"
CD	Cutout Diameter	4.2 in.	+/- 0.020"
MG	Magnet Diameter	3.4 in.	+/- 0.050"
HD	Hole Diameter	0.2 in.	+/- 0.010"
MD	Mounting Diameter	4.7 in.	+/- 0.010"
ID	Internal Depth	2.2 in.	+/- 0.025"
FT	Flange Thickness	0.1 in.	+/- 0.050"
NW	Net Weight	918.0 g	

