

The TK-101 system is a great choice for kiosks and digital signage, as well as entry-level gaming applications. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers. While low in cost, the 101 provides plenty of high-intelligibility sound output thanks to the perfect match of the amplifier to the speakers.

Speakers

- 2 x 3.5 inches (50 x 90mm) wide range
- 8-Ohm, 10 Watt, 84dB sensitivity
- Shielded magnet prevents interference with electronic circuits and video displays
- Acrylic-treated cone surround for long life
- Speakers are not self-enclosed - will require mounting in cabinet with grilles



Amplifier

- Power output: 12.5W x 2
- PCB style
- Volume control
- Cool running and reliable Class D operation
- Wide 9-24VDC voltage input range
- Available MISCO power supplies: 36174 or PS15-VDC (sold separately)

This kit includes:

- Satellite Speaker - 84157 (x2)
- Amplifier - [93101](#)
- Wire Harness - 36173

Primary Specifications

Speaker System Type	Full Range
Enclosed Woofer Style	None
Subwoofer Type	None
Digital Signal Processing	No
Audio Signal Input	Analog

Primary Specifications

8 Ω both HF channels driven (Watts RMS)	13.5 W
Total Low Frequency (Sub-woofer) Output Power per channel into 4 Ω. (Watts)	9.5W
Digital Input S/PDIF	No

Dimensions & Weight

PCB Size (HxWxL) (mm)	0.6" x 2.25" x 2.5" (15.3 mm x 57.1 mm x 63.7 mm)
------------------------------	---

Power Supply Specifications

Barrel Plug Connector Size (mm)	2
--	---

