

The TK-301 system is a great choice for kiosk and gaming cabinets and enclosures ready to accept unenclosed speakers and amplifier. Its 5-1/4" woofer is optimized for infinite baffle (not enclosed) use. The PC board style amplifier is ready to be integrated alongside your electronics package. A supplied wiring harness with slip-on connectors makes assembly easy, foolproof and fast. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers.

Satellite Speakers

- 2" x 3.5" (50mm x 90mm) oval wide range driver
- 8-Ohm, 9-Watt, 87 dB sensitivity
- Neodymium magnet

Subwoofer

- 5.25" paper cone with Polyether foam surround
- 8-Ohm, 50-Watt, 87 dB sensitivity
- Infinite baffle mounting, no enclosure needed

Amplifier

- 2.1 Channel Amp, 50W, PCB Style, with DSP
- Up to 62W total power output
- Cool running, reliable Class D operation
- Integrated DSP for maximum sound control (EQ, Crossover and dynamic range control)

This kit includes:

- Satellite - 84160 (x2)
- Subwoofer - 82129
- Amplifier - [93104](#)
- Wire Harness - 36172



Primary Specifications

Speaker System Type	2 Way
Enclosed Woofer Style	None
Subwoofer Type	Infinite Baffle (No enclosure)
Digital Signal Processing	Yes
Audio Signal Input	Analog

Primary Specifications

8 Ω both HF channels driven (Watts RMS)	HF: 8.5, LF: 32
Total Low Frequency (Sub-woofer) Output Power per channel into 4 Ω. (Watts)	HF: 15.2, LF: 32W
Digital Input S/PDIF	No

Dimensions & Weight

PCB Size (HxWxL) (mm)	0.75" x 4.25" x 2.5" (19 mm x 108 mm x 64 mm)
------------------------------	--

Power Supply Specifications

