

The TK-302 system is a great choice for cabinets and enclosures with integrated speaker grilles ready to accept unenclosed satellite and enclosed subwoofers. The PC board style amplifier is ready to be integrated alongside your electronics package. A supplied wiring harness with slip-on connectors makes assembly easy, foolproof and fast. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers.

Satellite Speakers

- Size, cone material wide range speaker
- 8-Ohm, 9 Watts, 88 dB sensitivity
- Neodymium magnet
- Cloth surround for long life

Subwoofer

- 4" (102 mm) sub-woofer
- 4 Ohm, 20 Watt, 85 dB sensitivity
- Wooden MDF (Medium Density Fiberboard) ported enclosure

Amplifier

- 2.1 Channel Amp, 60W, PCB Style, with DSP
- Up to 62W total power output
- Integrated DSP for maximum sound control (EQ, Crossover and dynamic range control)
- Cool running, reliable Class D operation
- 18V - 24V rail power supply
- Available MISCO power supply 36174 (sold separately)

This kit includes:

- Satellite - 84159 (x2)
- Subwoofer - [SB40-A](#)
- Amplifier - [93104](#)
- Wire Harness - 36155



Primary Specifications

Speaker System Type	2 Way
Enclosed Woofer Style	Ported
Subwoofer Type	Powered [active]
Digital Signal Processing	Yes
Audio Signal Input	Analog

Primary Specifications

Grille	Black
8 Ω both HF channels driven (Watts RMS)	HF: 8.5W, LF: 32W
Total Low Frequency (Sub-woofer) Output Power per channel into 4 Ω. (Watts)	HF: 15.2W LF: 32W
Digital Input S/PDIF	No

Dimensions & Weight

PCB Size (HxWxL) (mm)	0.75" x 4.25" x 2.5" (19 mm x 108 mm x 64 mm)
------------------------------	--

Power Supply Specifications

