

The TK-401 system is a great choice when you want the performance certainty and consistency of self-enclosed speakers. The PC board style amplifier is ready to be integrated alongside your electronics package. A supplied wiring harness with slip-on connectors makes assembly easy, foolproof and fast. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers.

#### Satellite Speakers

- 3" (76mm) Polypropylene cone wide range driver
- Neodymium magnet
- Rubber surround for long life
- Rigid glass-filled Injection molded enclosure

#### Sub-Woofer

- 5.25" paper cone woofer with Polyether foam surround
- 8-Ohm, 50-Watt, 87dB sensitivity
- Ported low-resonance MDF (Medium Density Fiberboard) enclosure

#### Amplifier

- 2.1 Channel amp, Class D, PCB style with DSP
- Cool-running, reliable Class D operation
- Up to 28W total power output
- Recommended power supply 24V DC
- Optional MISCO power supply 36162

Wiring harness with quick-connect terminations include

This kit includes:

- Satellite - 90201(x2)
- Subwoofer - [SB52-A](#)
- Amplifier - [93110](#)
- Wire Harness - 36155



#### Primary Specifications

<b>Speaker System Type</b>	2 Way
<b>Enclosed Woofer Style</b>	Ported
<b>Subwoofer Type</b>	Powered [active]
<b>Digital Signal Processing</b>	Yes
<b>Audio Signal Input</b>	Analog

**Primary Specifications**

<b>8 <math>\Omega</math> both HF channels driven (Watts RMS)</b>	20
<b>Total Low Frequency (Sub-woofer) Output Power per channel into 4 <math>\Omega</math>. (Watts)</b>	8
<b>Digital Input S/PDIF</b>	Yes

**Dimensions & Weight**

<b>PCB Size (HxWxL) (mm)</b>	0.72" x 4.25" x 6.38" (18 mm x 108 mm x 162 mm)
------------------------------	---

**Power Supply Specifications**

