

THIS IS A "BUILT TO ORDER" PRODUCT.

REQUEST A QUOTE

For a high compliance 4" driver resistant to corrosion and moisture, choose the JC5FD. This compact driver is ideal for low-level distribution systems looking for superior sound dispersion. A rugged steel frame and a treated cloth cone help support reliable sound while remaining environmentally resistant.

- Wide range speaker
- 4" (102 mm) steel basket diameter
- 15 watts, 8 ohms, 93 dB SPL
- 10 oz. ferrite magnet, treated cloth cone



Primary Specifications

| | |
|--|-------------|
| Size, Nominal (inch & mm) | 4" (100 mm) |
| Rated Impedance (Ω) | 8 |
| Sensitivity (dB SPL) ¹ | 93 |
| Frequency Range (Hz) | 60 - 12,000 |
| Resonant Frequency (Fs) (Hz) +/- 15% | 85 |

More Specifications

| | |
|--------------------------|---------------------------------------|
| Application | Indoor, Transit, Voice Communications |
| RoHS Compliant | No |
| Program Power (W) | 30 |

Small Signal Parameters

| | |
|--|------|
| Nominal Impedance (Z) (Ω) | 8 |
| Resonant Frequency (Fs) (Hz) +/- 15% | 85 |
| Total Q Factor (Qts) | 1.50 |

Material Descriptions

| | |
|---------------------------|---------------|
| Basket Type | Stamped steel |
| Magnet Material | Ferrite |
| Magnet Weight (g) | 283.5 |
| Cone Body Material | Treated cloth |

