

THIS IS A "BUILT TO ORDER" PRODUCT.

**REQUEST A QUOTE**

This high-performance OEM speaker is designed for outdoor communications, providing a clear and powerful voice projection with its high sensitivity rating. The speaker cone and surround have been waterproof treated, ensuring reliable operation even in harsh environments, and a square aluminum louvered grille adds additional environmental protection. Installation is made easy with the included 6" 16 AWG wire with a male 2-way packard connector.

- Voice range speaker
- 3" (77 mm) steel basket diameter
- 4 watts, 7 ohm, 93 dB SPL
- Waterproof cone & surround
- 2.35 oz. ferrite magnet
- 4.5" louvered aluminum grille
- 6" 16AWG wire, male 2-way connector



#### Primary Specifications

<b>Size, Nominal (inch &amp; mm)</b>	3" (77 mm)
<b>Sensitivity (dB SPL) <sup>1</sup></b>	93
<b>Frequency Range (Hz)</b>	600 - 9,000
<b>Resonant Frequency (Fs) (Hz) +/- 15%</b>	1100

### More Specifications

<b>Application</b>	Outdoor , Voice Communications
<b>RoHS Compliant</b>	No
<b>DC Resistance (Re) (<math>\Omega</math>)</b>	6.3
<b>Program Power (W)</b>	8

### Small Signal Parameters

<b>Nominal Impedance (Z) (<math>\Omega</math>)</b>	7
<b>DC Resistance (Re) (<math>\Omega</math>)</b>	6.3
<b>Resonant Frequency (Fs) (Hz) +/- 15%</b>	1100

### Material Descriptions

<b>Basket Type</b>	Stamped steel
<b>Voice Coil Diameter (mm)</b>	14
<b>Voice Coil Wire Material</b>	Copper
<b>Voice Coil Former Material</b>	Kapton
<b>Magnet Material</b>	Ferrite
<b>Magnet Weight (g)</b>	67
<b>Cone Body Material</b>	Treated paper
<b>Cone Surround Material</b>	Foam
<b>Net Weight (kg)</b>	0.29

