



A 5.25" reentrant horn speaker with a 7.5" mounting flange designed for indoor or outdoor paging audio and voice communication systems. This compact design is for recessing in walls or ceilings. A durable phenolic-impregnated cloth dome ensures reliability even in high-humidity situations.

- 5" metal flange mounted reentrant horn
- 1" (28 mm) durable phenolic diaphragm
- Designed for recess mounting
- 20 watts, 8 ohm, 100 dB SPL
- Powerful 70 mm ferrite magnet
- Transformer not included in this model

MISCO engineers use the world's most sophisticated loudspeaker measurement systems, including the Klippel Analyzer, to maximize and validate the speaker's design, as well as the Klippel QC module to ensure perfect unit-to-unit consistency and reliability.



### Primary Specifications

<b>Size, Nominal (inch &amp; mm)</b>	8" (203 mm)
<b>Sensitivity (dB SPL) <sup>1</sup></b>	100
<b>Resonant Frequency (Fs) (Hz) +/- 15%</b>	1150

### More Specifications

<b>Application</b>	Voice Communications
--------------------	----------------------

### Small Signal Parameters

<b>Nominal Impedance (Z) (<math>\Omega</math>)</b>	8
<b>Resonant Frequency (Fs) (Hz) +/- 15%</b>	1150

### Material Descriptions

<b>Magnet Material</b>	Ferrite
------------------------	---------

